



ALIZE' 22-48T



ALIZE' 164



General characteristics :

ALIZE' : series of small cabinets for the programmed leavening. For 60x40 trays and racks

- Structure : Modular self holding panels, insulated with 70mm high density (41kg/m³) expanded polyurethan. Air convection system by means of modular, stainless steel group, easy to disassemble and clean. Internal kit with stainless steel guard guides for inserting the trolleys.
- Internal coating : Stainless steel AISI 304 18/10
- External coating : Goffered pre-painted galvanized sheet
- Floor : Isolated with a panel of mm. 70 thickness and reinforced with plastified metal sheet. Entry high capacity ramp in stainless steel 18/8.

Control

- Electronic control panel for the set-up of the programmed stop leavening
- 7 independant programs and 3 manual functions to control cold & hot cycle, baking delay
- 7 programs capable of controlling the following cycles :
 - Quick freezing and stop-leavening
 - Pre-leavening
 - 2 steps of leavening
 - Baking delay
 - Climatized temperature control, humidity probe control, buffer memory of the program in case of black-out

Code	Model	Temp. °C	Dimensions cm.	Door cm.	Nr. of trays	Electric Kw
07 ALZ 2064	ALIZE' 20T	-6°/ +35°	78x70x205h	66x145h	20 (60x40)	230/50/1ph 1,2
07 ALZ 4864	ALIZE' 48T	-10°/ +40°	97x97x237h	61x80h (2)	24 (60x80) 48 (60x40)	230/50/1ph 2

Code	Model	Temp. °C	Dimensions cm.	Door cm.	Nr. of racks	Electric Kw
07 ALZ 164	ALIZE' 164	-10°/ +40°	73x80x210h	66x170h	1 rack 62x47x150h	230/50/1ph 1,2
07 ALZ 264	ALIZE' 264	-10°/ +40°	117x137x237h	80x190h	2 racks 62x47x185h	230/50/1ph 1,4