


General characteristics :

VENDAVAL: series of large size cabinets for the programmed leavening. For trays 60x80 on racks cm. 67x82x195h

- Structure : Modular self holding panels, insulated with 70mm high density (41kg/m³) expanded polyurethan. Air convection system by means of modular, stainless steel group, easy to disassemble and clean. Internal kit with stainless steel guard guides for inserting the trolleys.
- Internal coating : Stainless steel AISI 304 18/10
- External coating : Goffered pre-painted galvanized sheet
- Floor : Isolated with a panel of mm. 70 thickness and reinforced with plastified metal sheet. Entry high capacity ramp in stainless steel 18/8.

Code	Model	Temp. °C	Dimensions cm.	Doors cm.	Nr. of racks	Electric kw
07 VDL 468	VENDAVAL 468	-10°/ +40°	257x157x257h	95x200h (2)	4 rack 67x82x195h 6 racks	400/50/3ph 4
07 VDL 668 07 VDL 481	VENDAVAL 668 VENDAVAL 481	-10°/ +40°	257x237x257h	95x200h (2)	67x82x195h 4 racks 85x102x195h	400/50/3ph 6
07 VDL 868	VENDAVAL 868	-10°/ +40°	257x297x257h	95x200h (2)	8 racks 67x82x195h	400/50/3ph 8
07 VDL 681	VENDAVAL 681	-10°/ +40°	257x337x257h	95x200h	6 racks 85x102x195h	400/50/3ph 8,5
07 VDL 1068	VENDAVAL 1068	-10°/ +40°	257x357x257h	95x200h (2)	10 racks 67x82x195h	400/50/3ph 10
07 VDL 1268	VENDAVAL 1268	-10°/ +40°	257x437x257h	95x200h (2)	12 racks 67x82x195h	400/50/3ph 12

Control

- Electronic control panel for the set-up of the programmed stop leavening
- 7 independent programs and 3 manual functions to control cold cycle, hot cycle, baking delay
- 7 programs capable of controlling the following cycles :
 - Quick freezing and stop-leavening
 - Pre-leavening
 - 2 steps of leavening
 - Baking delay
 - Climatized temperature control, humidity probe control, buffer memory of the program in case of black-out

